


Fire resistant cables

 SHENXING CABLE GROUP



APPLICATION



Fire retardant



Safe&reliable



Sustainable



Corrosion resistance

BTTZ Copper core copper sheathed magnesium oxide mineral insulated cable

Conductor: 99.99%copper

Insulation: Magnesium oxide

Metal sheath: Copper Tube

Rated voltage: UO/U 0.6/1kV

Number of cores: 1、 2、 3、 4、 5、 3+1、 4+1、 3+2

Nominal cross-sectional area 1.5-400mm²

Accept Customization



BTTVZ Copper core copper sheathed magnesium oxide mineral insulated fireproof cable

Conductor: 99.99%copper

Insulation: Magnesium oxide

Metal sheath: Copper Tube

Jacket: WDZR PE

Rated voltage: UO/U 0.6/1kV


Number of cores: 1、 2、 3、 4、 5、 3+1、 4+1、 3+2

Accept Customization



Fire resistant cables

 SHENXING CABLE GROUP



BBTRZ Flexible magnesium hydroxide mineral insulated fire resistant cable

Conductor: 99.99% copper

Insulation: Multi-layer mica tape+XLPE

Fireproof layer: magnesium hydroxide

Outer sheath: low smoke halogen-free flame retardant PE

Rated voltage: UO/U 0.6/1kV

Number of cores: 1、2、3、4、5、3+1、4+1、3+2

Accept Customization



NG-A (BTLY) Aluminum sheathed flexible isolation type fireproof cable

Conductor: 99.99% copper

Insulation: Multi-layer mica tape

Metal sheath: Aluminum tube+XLPE

Fireproof layer: magnesium oxide

Outer sheath: low smoke halogen-free flame retardant PE

Rated voltage: UO/U 0.6/1kV

Number of cores: 1、2、3、4、5、3+1、4+1、3+2

Accept Customization



YTTW Flexible fireproof metal sheathed inorganic mineral insulated cable

Conductor: 99.99% copper

Outer sheath: corrugated copper sheath

Rated voltage: UO/U 0.6/1kV


Number of cores: 1、2、3、4、5、3+1、4+1、3+2

Accept Customization



Fire resistant cables

 SHENXING CABLE GROUP



BTTRZ (RTTZ) Copper core inorganic mineral insulation tape wrapped insulation copper sheathed flexible fireproof cable

Conductor: 99.99%copper

Insulation: Multi-layer mica tape

Armor: Corrugated copper sheath

Outer sheath: low smoke halogen-free flame retardant PE

Rated voltage: UO/U 0.6/1kV

Number of cores: 1、 2、 3、 4、 5、 3+1、 4+1、 3+2

Accept Customization



YTSY Ultra-flexible mineral fire-resistant cable

Conductor: 99.99%copper

Insulation: Low smoke halogen-free flame retardant PE

Fireproof layer: magnesium oxide

Outer sheath: low smoke halogen-free flame retardant PE

Rated voltage: UO/U 0.6/1kV

Number of cores: 1、 2、 3、 4、 5、 3+1、 4+1、 3+2

Accept Customization

